



## DFB & DBR Laser Diodes

Distributed Feedback (DFB) and Distributed Bragg Reflector (DBR) laser diodes feature a frequency-selective structure within the laser chip, which restricts the laser emission to a single longitudinal mode. The lasing wavelength is tuned by varying either the driver current or the chip temperature. Single-frequency operation is usually maintained over several hundred GHz without any mode-hops.

In the table below, WL indicates the design wavelength. P is the maximum output power of the diode. WLmin and WLmax denote the wavelength range accessible via temperature tuning and dL/dT is the thermal tuning coefficient in nm/K.

Note that the range between WLmin and WLmax is usually, but not always, mode-hop free. If your application requires guaranteed mode-hop-free tuning, please inquire with TOPTICA Photonics. Further information e.g. regarding electric tuning, fast modulation options, spectroscopic applications and locking to resonance lines is available upon request.

Diodes with a TO-3 or butterfly-type package include a built-in thermistor and thermoelectric cooler. For other diodes (5.6 mm or 9 mm housings), we recommend TOPTICA's patented ColdPack for precise temperature control.

WL nm	P mW	WLmin nm	WLmax nm	dL/dT nm/K	Linewidth $\Delta\nu$ in kHz	Article Number	Stock	Remark
633.4		633.2	633.6	0.04	2000	#LD-0633-0010-DBR-2	1	
633.9		633.7	634.1	0.04	2000	#LD-0633-0010-DBR-2	u.r.	
634.0		633.8	634.2	0.04	2000	#LD-0633-0010-DBR-1	2	
764.0	50			0.06		#LD-0764-0050-DFB-1	u.r.	TO-3 inquire for details
766.9	30	765.7	768.1	0.05		#LD-0767-0030-DFB-1	u.r.	
767.0	30			0.05		#LD-0767-0030-DFB-1	u.r.	inquire for details
769.9	60	769	770.8	0.06	<1000	#LD-0770-0060-DBR-1	u.r.	
770.1	60	769.2	771	0.06	<1000	#LD-0770-0060-DBR-1	u.r.	
778.0	60	777.1	778.9	0.06	<1000	#LD-0778-0060-DBR-1	1	
780.0	80	778.8	780.9	0.06		#LD-0780-0080-DFB-2	u.r.	For Rb spectroscopy [1], TO-3
781.0	80	779.8	781.9	0.06		#LD-0780-0080-DFB-2	u.r.	For Rb spectroscopy [1], TO-3
782.8	100	781.6	784	0.06		#LD-0783-0080-DFB-1	u.r.	For THz applications, TO-3
784.2	100	783	785.4	0.06		#LD-0785-0080-DFB-1	1	For THz applications, TO-3
784.4	100	783.2	785.6	0.06		#LD-0785-0080-DFB-1	u.r.	For THz applications, TO-3
784.4	120	783.3	785.5	0.05		#LD-0785-0120-DFB-1	1	

[1] Note: The diodes reach the target wavelengths for Rb/Cs spectroscopy, though not necessarily at the center of the tuning range.

u.r. : upon request



## DFB &amp; DBR Laser Diodes

WL nm	P mW	WLmin nm	WLmax nm	dL/dT nm/K	Linewidth $\Delta\nu$ in kHz	Article Number	Stock	Remark
795.0	120	793.8	796.2	0.07	1000	#LD-0795-0120-DBR-2	u.r.	For Rb spectroscopy [1]
851.6	140	850.6	852.6	0.06		#LD-0852-0150-DFB-1	1	For Cs spectroscopy [1], TO-3
852.3	140	851.1	853.8	0.06		#LD-0853-0150-DFB-1	u.r.	For THz applications, TO-3
852.4	140	851.4	853.4	0.06		#LD-0852-0150-DFB-1	u.r.	For Cs spectroscopy [1], TO-3
852.4	140	851.2	853.9	0.06		#LD-0853-0150-DFB-1	u.r.	For THz applications, TO-3
852.6	140	851.4	854.1	0.06		#LD-0853-0150-DFB-1	u.r.	For THz applications, TO-3
852.7	140	851.5	854.2	0.06		#LD-0853-0150-DFB-1	u.r.	For THz applications, TO-3
852.8	140	851.6	854.3	0.06		#LD-0853-0150-DFB-1	u.r.	For THz applications, TO-3
853.2	140	852	854.7	0.06		#LD-0853-0150-DFB-1	u.r.	For THz applications, TO-3
853.3	140	852.1	854.8	0.06		#LD-0853-0150-DFB-1	u.r.	For THz applications, TO-3
853.4	140	852.2	854.9	0.06		#LD-0853-0150-DFB-1	u.r.	For THz applications, TO-3
853.5	140	852.3	855	0.06		#LD-0853-0150-DFB-1	u.r.	For THz applications, TO-3
853.6	140	852.4	855.1	0.06		#LD-0853-0150-DFB-1	u.r.	For THz applications, TO-3
895.0	40	893.8	896.2	0.07	1000	#LD-0895-0040-DBR-1	u.r.	For Cs spectroscopy [1]
911.6	25	910.6	912.6	0.08		#LD-0910-0025-DFB-1	1	Special offer - limited stock!
935.2	30	935.1	936.5	0.08		#LD-0935-0030-DFB-1	u.r.	
1053.0	30			0.1		#LD-1053-0030-DFB-1	u.r.	Butterfly + pigtail inquire for details
1056.2	40	1055.2	1057.5	0.08		#LD-1055-0040-DFB-1	1	
1064.0	30	1062.1	1066.2	0.1		#LD-1064-0030-DFB-1	2	Butterfly + pigtail
1178.0	20	1177.5	1179.5	0.09		#LD-1178-0030-DFB-1	u.r.	ellipse 5:1
1178.3	30	1176.4	1180.5	0.1		#LD-1178-0030-DFB-3	u.r.	Butterfly + pigtail
1228.0	25	1226	1229	0.1		#LD-1230-0030-DFB-1	1	Special offer - limited stock!
1266.0	20	1263	1269	0.1	2000	#LD-1266-0020-DFB-1	2	Butterfly, PM Pigtail
1278.2	10	1274.2	1278.3	0.1		#LD-1280-0010-DFB-1	1	Special offer - limited stock!
1310.0	30	1308	1312	0.1		#LD-1310-0030-DFB-1	u.r.	Butterfly, PM Pigtail

[1] Note: The diodes reach the target wavelengths for Rb/Cs spectroscopy, though not necessarily at the center of the tuning range.

u.r. : upon request



## DFB &amp; DBR Laser Diodes

WL nm	P mW	WLmin nm	WLmax nm	dL/dT nm/K	Linewidth $\Delta\nu$ in kHz	Article Number	Stock	Remark
1315.0	20	1314	1316		2000	#LD-1315-0020-DFB-1	u.r.	Butterfly + pigtail
1377.2	12	1374	1378	0.1		#LD-1375-0015-DFB-1	1	Special offer - limited stock!
1395.0	10			0.1	2000	#LD-1395-0010-DFB-1	u.r.	Butterfly, PM Pigtail inquire for details
1533.0	40	1531.1	1535.2	0.1	<1000	#LD-1550-0040-DFB-1	3	Butterfly + pigtail
1537.8	40	1535.9	1540	0.1	<1000	#LD-1550-0040-DFB-1	1	Butterfly + pigtail
1550.0	80	1547.8	1552.2	0.11	<1000	#LD-1550-0080-DFB-1	u.r.	Butterfly + pigtail
1572.0	60	1569.9	1574.1	0.1	<1000	#LD-1550-0060-DFB-1	1	Butterfly + pigtail
1652.0	10	1650	1655	0.13		#LD-1665-0010-DFB-1	u.r.	Butterfly + pigtail
1661.5	6	1660.5	1662.5		2000	#LD-1660-0005-DFB-1	u.r.	Butterfly, PM Pigtail
2004.0	2	2002	2005	0.1		#LD-2000-0003-DFB-1	u.r.	Butterfly, PM Pigtail
2410.0	2	2406	2411	0.24		#LD-2410-0004-DFB-1	u.r.	
2723.0	2	2718.2	2725.2	0.23		#LD-2740-0003-DFB-1	u.r.	

[1] Note: The diodes reach the target wavelengths for Rb/Cs spectroscopy, though not necessarily at the center of the tuning range.

u.r. : upon request